



www.soflooring.com

Lee Floorstok
Unit B1 The Dresser Centre
Whitworth Street
Manchester
M11 2NE
Tel: 0161 231 8080
Fax: 0161 231 8787
Email: leefloor@aol.com
Web: leefloorstok.com

Product Data Sheet

SO PRIME

FAST DRYING DISPERSION PRIMER



Features

- Prolongs smoothing compounds flow life and workability.
- Interior and exterior use.
- Water-based and non-flammable.
- Dries almost transparent, will not stain.
- Reduces porosity of surfaces.

Description

SO Prime – An acrylic dispersion specially formulated to improve adhesion and inhibiting penetration of water in intermittently damp locations. **SO Prime** is used as a pore sealer on floor surfaces to prevent air bubbles rising through subsequently applied sub-floor smoothing compounds and to prolong their flow life and workability. Ideal for priming cement sand renders, screeds and concrete surfaces prior to the application of ceramic tile adhesives.

Application

Shake container well before use. Dilute if required. Apply the primer evenly, using a brush or broom, over the sound, clean and dust-free surface and leave to dry to a clear thin film.

System 1 – Slurry Priming

A most effective primer for all cement based adhesives and screeds, internally and externally, is to brush tightly onto the surface a thin even layer of a well stirred mixture of:- 1 volume water, 1 volume **SO Prime**, 1 volume of cement based product that will then be used. The layer should normally be allowed to set for a few hours before work progresses. Coverage: Approximately 6 sq. metres per litre of **SO Prime**.

System 2 – Priming/Sealing exterior

For the simple priming/sealing of all cementitious and other surfaces particularly for exterior work, brush into the surface a thin even layer of a blend of:- 4 volumes water, 1 volume **SO Prime** mixed by thorough stirring. Allow layer to dry slightly before applying smoothing compounds or adhesives. Coverage: Approximately 30 sq. meters per litre of **SO Prime**.

System 3 – Priming/Sealing interior

For the simple priming/sealing of most interior surfaces brush apply a thin even layer of a blend of:- 4 volumes water, 1 volume **SO Prime** mixed by thorough stirring. Allow layer to thoroughly dry before continuing. Coverage: Approximately 30 sq. meters per litre of **SO Prime**.

Health & Safety Advice

SO Prime is Non Irritant but irritation may occur if dried material adheres to the skin, avoid contact with skin, eyes and clothing. Do not swallow. Wear suitable protective clothing, chemical resistant gloves and eye/face protection. Keep away from children.

The relevant Material Safety Data Sheet is available on request.

Application Data	
Size	5 Ltr
Packaging	Polyethylene containers Protect from frost and direct sunlight
Walk on time @ 20°C	Touch dry and not transferred to shoes
Installation Temperature	Minimum 5°C
Shelf Life	Has a storage life of not less than 12 months in the original unopened containers.