


www.soflooring.com

Lee Floorstok Unit B1 The Dresser Centre Whitworth Street Manchester M11 2NE Tel: 0161 231 8080 Fax: 0161 231 8787 Email: leefloor@aol.com Web: leefloorstok.com

## **Technical Data Sheet**

# SO DIM 6



## PVC RAMP EDGE TRIM

#### **Description**

SO DIM 6 is a flexible pvc ramp edge profile which provides a neat and simple solution to joining floorcoverings of different heights. It is typically used to join carpet to terazzo or stone floors. Suitable for use with 6mm carpet or carpet tile (compressed thickness). The compressed thickness of the carpet should be a flush finish to the gauge of the profile.

#### **Installation**

SO DIM 6 ramp edge trim should be allowed to acclimatise for 24 hours prior to installation at an ambient temperature of 18° Celsius.

- It should be ensured that all surfaces to which the profile is to be fixed are dry, flat and free from any contaminants.
- 2. Cut the profile to the size required.
- 3. Apply a proprietary contact adhesive to the underside of the profile and the floor
- 4. Allow the adhesive to become touch dry.
- 5. Install the carpet up to the back of the profile ensuring the carpet is sealed if necessary

#### **Cleaning and maintenance guidelines:**

These guidelines have been compiled to help the user obtain optimum performance and satisfaction.

### **Preventative Maintenance Programme**

A regular scheduled maintenance programme should be employed to prevent the build up of dirt and grease, which will detract from the overall appearance of the product.

#### **Daily Cleaning**

 Brush down the profile using a soft bristled brush and remove dust particles by wiping with a damp cloth.

#### Twice Weekly or as Required

Brush down the profile using a soft bristled brush. With clean warm water, apply a small
amount of a soap-less detergent to a lint free cloth and gently clean the surface. During
the clean, the water must be changed on a regular basis. Once the profile has been
cleaned thoroughly rinse with fresh, clean water and dry with a dry lint free cloth.
On completion the profile should be completely dry.

NB. The use of an aggressive detergent could result in colour fade within the PVC. Floor sealants, polishes or such coating should not under any circumstances be applied to PVC.

Technical Data	
Type:	Ramp Edge Trim
Environment:	Interior
Used with:	Carpet & Carpet Tile
Material:	PVC
Width	40mm
Gauge:	6mm
Length:	2.0m
Colour:	Black
Fixing:	Adhesive Fix

