



www.soflooring.com

Lee Floorstok
Unit B1 The Dresser Centre
Whitworth Street
Manchester
M11 2NE
Tel: 0161 231 8080
Fax: 0161 231 8787
Email: leefloor@aol.com
Web: leefloorstok.com

Safety Data Sheet

SO FAST 30

RAPID SETTING SMOOTHING COMPOUND
LATEX SCREED POWDER



1. IDENTIFICATION OF SUBSTANCE/PREPARATION AND COMPANY

| | |
|---------------|--|
| PRODUCT NAME | SO FAST 30 - LATEX SCREED POWDER |
| SUPPLIER NAME | N&C Building Products Limited |
| ADDRESS | 41 – 51 Freshwater Road Chadwell Heath, Romford Essex RM8 1SP |
| TELEPHONE | 020 8586 4600 |
| FAX | 020 8586 4646 |

2. HAZARDS IDENTIFICATION

The product is abrasive, alkaline when mixed with water, and can cause burns on prolonged contact. It contains a small percentage of respirable silica. Contains Chromium vi, addition of a reducing agent ensures this remains below 2ppm during the shelf life of the product. May produce an allergic reaction.
Hazard Designation Xi Irritant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition: Product is a blend of Hydraulic Cements, Inorganic Minerals and Organic Additives.

4. FIRST AID MEASURES

| | |
|---|--|
| EYE CONTACT minutes. | Powder or wet adhesive irritates eyes. Irrigate immediately with water for at least 10 Seek medical attention if irritation persists |
| SKIN CONTACT re-use. dermatitis. Seek | Avoid skin contact with wet product. Remove contaminated clothing and wash before Wash off with copious quantities of water. Frequent, persistent use may cause medical attention for persistent irritation. |
| INHALATION | If any effects occur, remove to fresh air and seek medical advice |
| INGESTION | Do not induce vomiting. Seek medical advice. |

Product Data Sheet

SO FAST 30

RAPID SETTING SMOOTHING COMPOUND
LATEX SCREED POWDER



5. FIRE FIGHTING MEASURES

| | |
|-------------------------------|---------------------------|
| EXTINGUISHING MEDIA | Product is non flammable. |
| EXPOSURE HAZARDS | Not Applicable |
| PERSONAL PROTECTIVE EQUIPMENT | Not Applicable. |

6. ACCIDENTAL RELEASE MEASURES

| | |
|-------------------------------|--|
| PERSONAL PROTECTIVE EQUIPMENT | Wear suitable gloves and safety goggles if eye contact is likely. |
| ENVIRONMENTAL CONSIDERATIONS | Dry powder should be scooped up and disposed of according to national or regional regulations. Avoid formation of dust. Wet product may be scraped up. |
| SPILLAGE REMOVAL | Dried product may be disposed of by landfill, according to Local Authority Regulations. |

7. HANDLING & STORAGE

| | |
|----------|--|
| HANDLING | Avoid contact with skin, eyes and clothing. Do not let wet product dry on skin, clothes etc., as it may cause burns. |
| STORAGE | Store in a cool dry place. |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

| | |
|------------------------|---|
| ENGINEERING MEASURES | Ensure adequate ventilation. |
| RESPIRATORY PROTECTION | Respiratory protection should not be required when product is used as intended. |
| SKIN/HAND PROTECTION | Wear suitable gloves if or use a barrier cream to prevent contact. |
| EYE PROTECTION | Safety spectacles are recommended as a minimum eye protection. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---------------------|--|
| FORM | Powder |
| COLOUR | Grey |
| ODOUR | Slight |
| pH | Approx 13 in aqueous phase |
| BOILING POINT/RANGE | Not Applicable |
| VAPOUR PRESSURE | Not Applicable |
| SOLUBILITY - WATER | Product is mixed with water before use |
| BULK DENSITY | Approximately 1600 Kg/m ³ |
| AUTO FLAMMABILITY | Not applicable |
| EXPLOSIVE PROPERTY | Not applicable |

Product Data Sheet

SO FAST 30

RAPID SETTING SMOOTHING COMPOUND
LATEX SCREED POWDER



10. STABILITY AND REACTIVITY

| | |
|----------------------------------|---|
| STABILITY | The product is stable under ambient conditions of temperature and pressure. Avoid freezing. |
| MATERIALS TO AVOID | Acids |
| HAZARDOUS DECOMPOSITION PRODUCTS | None under normal use. Produces carbon dioxide in contact with acids. |

11. TOXICOLOGICAL INFORMATION

| | |
|------------|--|
| INHALATION | Irritant. |
| INGESTION | Irritant |
| SKIN | Prolonged contact may cause irritation, especially with wet material. |
| EYE | Powder or wet product irritates eyes. May cause irritation due to mechanical action. |

12. ECOLOGICAL INFORMATION

| | |
|------------------|---|
| AQUATIC TOXICITY | Avoid contaminating water and wastewater. Water hazard class 1: slightly hazardous. Do not let large quantities to reach ground water, rivers, drainage or sewer systems. Soil and groundwater in contact freshly set or hardened mortar may become alkaline. |
| BIODEGRADABILITY | Not determined |

13. DISPOSAL CONSIDERATIONS

The recommended procedure for disposal is burying on an approved landfill. Dispose of material according to applicable national or regional regulations.

14. TRANSPORTATION INFORMATION

| | | |
|---|--------------|----------------|
| Classification, Packaging & Labeling Requirements | | |
| SEA: | IMDG. CLASS: | Not Restricted |
| ROAD: | ADR CLASS: | Not Restricted |
| AIR: | IACO CLASS: | Not Restricted |
| RAIL: | RID CLASS: | Not Restricted |

15. REGULATORY INFORMATION

HAZARD CATEGORY:

| | |
|----------------|--|
| Risk Phrases | R36/37/38 Irritating to Eyes, Respiratory System and Skin |
| Safety Phrases | S2 Keep out of the reach of children S24 Avoid contact with skin S25 Avoid contact with eyes S26 In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice. S28 After contact with skin, wash immediately with plenty of clean water. S36-39 Wear suitable protective clothing, gloves and eye protection. |

These products have been classified Xi, Irritant.

SO FAST 30

RAPID SETTING SMOOTHING COMPOUND
LATEX SCREED POWDER



16. OTHER INFORMATION

While N&C Building Products Ltd. endeavours to ensure that all advice given relating to the use and/or application of our products (whether in this leaflet or otherwise) is both correct and useful, the information is based partly on data made available to us from other sources and is not guaranteed as accurate.

It is not intended in any way to be exhaustive or as a substitute for the customer's own product testing, evaluation and safety procedures.

If you have any queries over the suitability of safety precautions required for your particular application, please contact us and we will endeavour to assist you further. Customers who make use of the product without contacting us do so at their own risk.

The information contained in this leaflet is under continuous review and liable to be modified from time to time.

Hazard Data Sheet
Revision No : 02
Dated : 05/11/2009